Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Double Row Terminal Blocks

Kulka® 601 GP Series

300 Volts

Jameco Part Number 188664

Specifications:

Base, General Purpose Phenolic, 150° C
JJ (GDI-30F) material is available
Open Back Design
Screws, #6-32 Binder Head, Phil-Slot
Terminals, Plated Brass
1-23 Poles
7/16" Centers
Wire Range with Wire Binding Screw #12 - #22 Awg - 20 Amps
Will Accommodate Lugs for Wire Sizes #10 - #16 Awg - 30 Amps
The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application.
UL Recognized File No. E47811
CSA Certified File No. LR19766
CE

Catalog #	# of poles	Dimensions	
		A	B
601 GP 01	1	1.19	0.88
601 GP 02	2	1.62	1.31
601 GP 03	3	2.06	1.75
601 GP 04	4	2.50	2.19
601 GP 05	5	2.94	2.63
601 GP 06	6	3.37	3.06
601 GP 07	7	3.81	3.50
601 GP 08	8	4.25	3.94
601 GP 09	9	4.69	4.38
601 GP 10	10	5.12	4.81
601 GP 11	11	5.56	5.25
601 GP 12	12	6.00	5.69

Top Mounted Hardware is .250" Wide

Catalog #	# of poles	Dimensions	
		A	B
601 GP 13	13	6.44	6.13
601 GP 14	14	6.87	6.56
601 GP 15	15	7.31	7.00
601 GP 16	16	7.75	7.44
601 GP 17	17	8.19	7.88
601 GP 18	18	8.62	8.31
601 GP 19	19	9.06	8.75
601 GP 20	20	9.50	9.19
601 GP 21	21	9.94	9.63
601 GP 22	22	10.37	10.06
601 GP 23	23	10.81	10.50

MM=Dim X 25.4

Hardware Options:

KT 37	=	Full Quick Connect (0° flat)	See Page 87
KT 38	=	Full Quick Connect (45° Bend)	See Page 87
KT 39	=	Full Quick Connect (90° Bend)	See Page 87
ST	=	Full Solder	See Page 88
LL(J601)	=	Line to Line Jumper	See Page 90
3/4 ST	=	Half Solder	See Page 88
KT 43	=	Half Quick Connect (0° Flat)	See Page 87
KT 44	=	Half Quick Connect (45° Bend)	See Page 87
KT 45	=	Half Quick Connect (90° Bend)	See Page 87
3765	=	Wire Clamp Screw	See Page 90
Y	=	Feed Thru Solder (.422)	See Page 89
YSY	=	Feed Thru Solder (.687)	See Page 89
2102	=	Stud	See Page 92
2104	=	Feed Thru Solder	See Page 92
2108	=	Individual Screw Terminals	See Page 92